

ANALYSIS OF CERTIFICATE

Producer:	ZHEJIANG JIUTENG PACKAGE MATERIALS CO.,LTD			
Film name:	High performance Polyolefin shrink film,5layers co-extrusion,			
Composition:	LLDPE(75%) PP(25%)			
Diameter of inside core:	76.2mm			
Film Size:		15mic*12inch*1335m	15mic*16inch*1335m	19mic*18inch*1070m
Thickness(um)		14.9	14.9	18.9
Width(mm)		310	420	470
Tensile Strength(N/mm ²)	MD	76	76	69
	TD	66	66	64
Elongation(%)	MD	101	101	94
	TD	94	94	86
Tear propagation(g)	MD	16.6	16.6	24.1
	TD	16.1	16.1	23.1
Hot wire seal热封强度	MD	0.85	0.85	1.05
	TD	0.82	0.82	1.01
Free shrinkage(130°C)	MD	69	69	68
	TD	68	68	66
COF(uD)	Dynamic	0.27	0.27	0.26
	Static	0.29	0.29	0.28
Haze(%)		4	4	4.4
Clarity(%)		98.1	98.1	97
Gloss@45Deg		84.1	84.1	84
Oxygen transmission Rate		11700	11700	9600
Water Vapor Transmission Rate		46	46	39

浙江九腾包装材料有限公司
ZHEJIANG JIUTENG PACKAGING CO.,LTD

